



4320 Aerotech Center Way
Paso Robles, CA 93447
Telephone: (800) 350-2223 Fax: (805) 238-4201
PAGE 1 OF 1 Page Rev. Date: 11/14/22
P/N: 712505T

LS SERIES GEN. 5 MANUAL TRANS. CONVERSION KIT (.400" RECESSED CRANK)

KIT CONSISTS OF:

| No. | Qty | Part No. | Description |
|-----|-----|-----------|-----------------------------------|
| 1. | 1 | CF720001 | 168 FLYWHEEL |
| 2. | 8 | 716141A | 11mm FLYWHEEL BOLTS |
| 3. | 1 | CF165473S | CLUTCH ASSY. 11" |
| 4. | 1 | 716314 | T/O BEARING |
| 5. | 1 | 716155 | PILOT BUSHING SPACER |
| 6. | 1 | 716175 | T/O BEARING COLLAR |
| 7. | 5 | 720028 | 10mm X 1.5 BELLHOUSING BOLTS |
| 8. | 5 | 720038 | 10mm LOCKWASHER (for bhsg. bolts) |
| 9. | 6 | 723761 | XRP DOWEL BOLTS (pressure plate) |
| 10. | 1 | 383735 | 11" CLUTCH DISC |

OPTIONAL ITEMS:

P/N 716286 is a bracket that fits our NV4500 full bellhousings.
P/N 716213 slave cylinder fits this bracket.

Flywheel Installation
Engine Flywheel Bolts
* First Pass 15 lbs
* Second Pass 37 Lbs
* Final Pass 74 Lbs
Clutch Plate to Flywheel
*30 Ft. Lbs.

GENERAL INFORMATION:

Since the LS series flywheels only fit a LS series block and the engine crank is recessed .400", there are a couple of things that must be addressed. Usually our bellhousing kits include a new pilot bushing. A problem occurs because the 1.090" diameter that our bushings fit into on a standard GM is now .400" closer to the back of the block, creating a pilot bushing engagement problem. This kit comes with a pilot bushing spacer for the manual transmission applications. The spacer in this kit sets the pilot bushing in the correct location. **NOTE:** The groove on this bushing must be facing out when installed into the engine crank in addition the spacer and pilot bushing should be pressed together before installing into the engine.

The pressure plate and clutch disc are also included in this kit. These components are specifically designed for the LS series engine. The bolts have also been included to allow proper alignment of the pressure plate to the flywheel.

The release bearing in this kit is a custom bearing. When coupled to a stock transmission, the LS series engine used an internal hydraulic release bearing. Our full bellhousings are not compatible with the stock internal setup. This bearing design is manufactured to replace the internal bearing with a conventional bearing setup. **Do not use any other type of release bearing with this conversion. Premature clutch failure could occur.**

On Toyotas using a Marks 4WD Adaptor kit & our 712532 kit, the throw out bearing collar is not used.

SPECIAL NOTE: The components packaged in this kit have been assembled and machined for specific type of conversions. Modifications to any of the components will void any possible warranty or return privileges. If you do not fully understand modifications or changes that will be required to complete your conversion, we strongly recommend that you contact our sales department for more information. This instruction sheet is only to be used for the assembly of Advance Adapter components. We recommend that a service manual pertaining to your vehicle be obtained for specific torque values, wiring diagrams and other related equipment. These manuals are normally available at automotive dealerships and parts stores.